







Breathable



Water Repellent



Highly Polymer Modified

# **Fast Setting Instant Grab, Bead Adhesive For Masonry Substrates**

ecorend BA3 Fast Set Bead Adhesive is a highly polymer modified product that provides excellent adhesion and instant grab for bedding of render profile beads onto masonry substrates. The products can be applied in low temperatures by hand to set plastic and stainless-steel render beads prior to render application.

### **Approvals and Certificates**

EN-998-1:2016

#### **Technical Data**

Pack Size	25kg bag waterproof packaging
Finishing Tool	Trowel
Pot Life	30 minutes
Suitable Substrate	Concrete, Clay, Lightweight - Block and Brick
Water Demand	Approx. 5 to 5.75ltr per 25kg bag
Set Time	2 hours @ 20°C
Humidity Requirement	Less than 95%
Coverage	Approx. 80 linear metres per bag
Application Temperature	+3°C to 25°C

## **UK CA Declaration of Performance**



Wetherby Laroc Group Dalton Industrial Estate, Dalton, North Yorkshire YO7 3HE

#### ecorend BA3 Fast Set Bead Adhesive

GP: General purpose rendering/plastering mortar BS EN 998-1:2016

Reaction to fire	Class A1
Dry bulk density	1520 kg/m³
Compressive strength	CS IV
Adhesion	≥ 1.0 N/mm², (FP) B
Capillary water absorption	W2





