

### DECLARATION OF PERFORMANCE Number: CPR – 275/09

- Unique identification code of the product-type: **ecorend OCR One Coat Base**
- Type, batch or serial number or other identifying mark to identify the construction product as set out in Article 11 (4): **Batch Number: See product packaging**
- Intended use as foreseen by the manufacturer of the construction product in accordance with the harmonised technical specification: **Internal and external rendering on walls**
- Name, registered trade name or registered trademark and contact address of the manufacturer as set in article 11 (5): **Wetherby Laroc Group, Dalton Industrial Estate, Dalton, Thirsk, North Yorkshire YO7 3HE**
- Name and contact address of the authorised representative who has received a mandate for the tasks set out on Article 12 (2): **Not Relevant**
- System or systems for assessment and verification of constancy of performance of the construction product in accordance with annex V: **System 2+**
- In the case of declaration of performance concerning a construction product covered by a harmonised standard: **BS EN 998-1:2016 Specification for mortar for masonry Part 1: Rendering and plastering mortar**
- In the case of declaration of performance concerning a construction product for which a European Technical assessment has been issued: **Not Relevant**
- Declared performance

Reaction to fire	A1
Dry bulk density	1750 kg/m <sup>3</sup>
Compressive strength	CS IV
Adhesion	≥ 0.4 N/mm <sup>2</sup> , (FP) B
Capillary water absorption	W2
Water vapour permeability coefficient	μ ≤ 15/35 (BS EN 1745 Table A.12)
Thermal conductivity	(λ <sub>10, dry</sub> ) 0.82 W/mK (BS EN1745 Table A.12, mean value; P = 50%)

### UK CA MARKING according to UK CA CPR and BS EN 998-1:2016

<p>Wetherby Laroc Group Dalton Industrial Estate, Dalton, North Yorkshire YO7 3HE 14</p>	
<p>ecorend OCR One Coat Base</p> <p>GP: General purpose rendering/plastering mortar BS EN 998-1:2016</p>	
Reaction to fire	A1
Dry bulk density	1750 kg/m <sup>3</sup>
Compressive strength	CS IV
Adhesion	≥ 0.4 N/mm <sup>2</sup> , (FP) B
Capillary water absorption	W2
Water vapour permeability coefficient	μ ≤ 15/35 (EN 1745 Table A.12)
Thermal conductivity	(λ <sub>10, dry</sub> ) 0.82 W/mK (EN 1745 Table A.12, mean value; P = 50%)

- The performance of the product identified in points 1 and 2 is in conformity with the declared performance of point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

#### Signed for and on behalf of the manufacturer by:

Gavin Bagshaw – Technical Information & Customer Support Lead

(signature)

#### Place and date of issue:

5th September 2022 - Dalton/Thirsk