

Base Coat With Excellent Water Resistance, Breathability & Adhesion

ecorend OCR One Coat Base is a cement-based product, which is British Board of Agrément approved. A high-performance, W2 water repellent, versatile base coat that can be used as a scratch base coat ready to receive a through coloured render, or as a flat finish ready to receive a thin coat render. The product utilises our cutting-edge trowel technology which makes the product easy to apply by hand or by spray, in one coat.

Approvals and Certificates

BBA approved system 18/5592 & EN-998-1:2016

Technical Data

Pack Size	25kg Bag waterproof packaging
Application Tool	Stainless Steel Trowel, 6mm Notched Trowel, Sponge Float
Pot Life	1 hour+
Water Demand	Approx. 4 to 4.5ltr per 25kg bag
Ready to Finish	2 to 8 hours @ +3°C to 25°C
Humidity Requirement	Less than 95%
Coverage	Approx. 1.7kg per mm / per m ²
Application Temperature	+3°C to 25°C

Approved Substrates

Approved Substrates	Not Approved Substrates
New Concrete Block	Timber
Smooth Brick	Metal
Rough Brick	Glass
Hacked Off Render	Below DPC
	Flat Surfaces
	Existing Render
	Insulation
	Render Carrier Board

UK CA Declaration of Performance

UK CA	Wetherby Laroc Group Dalton Industrial Estate, Dalton, North Yorkshire YO7 3HE 14	
	ecorend OCR One Coat Base GP: General purpose rendering/plastering mortar EN 998-1:2010	
Reaction to fire	Class A1	
Dry bulk density	1750 kg/m ³	
Compressive strength	CS IV	
Adhesion	≥ 0.4 N/mm ² , (FP) B	
Capillary water absorption	W2	



Excellent Adhesion



Breathable



Water Repellent



Highly Polymer Modified

