

S10

Bonding Primer



Silicone Technology



Ready to Use



Excellent Adhesion



Water Based

PREPARATION

New build - Remove all loose and flaking material from the substrate, (typically mortar snots or site contamination and algae growth). This should be removed with a power wash and by cleaning the surface with a hard bristle brush.

APPLICATION

ecorend S10 Bonding Primer is applied with a roller, brush or spray.

STORAGE

When stored unopened in a dry place at temperatures above +5°C, shelf life is 18 months from date of manufacture.

TOOL CLEANING

All equipment must be washed with clean water immediately after use. Waste material should not be emptied into drainage systems.

HEALTH & SAFETY INSTRUCTIONS

This product contains a biocide for the protection of the cured product. Contains 2-OTYL 2HISOTHIAZOL-3-ONE. May produce an allergic reaction. For further information, please request the material safety data sheet for this product.

IMPORTANT INFORMATION

DO NOT apply if frost is forecast within 24 hours, in wet conditions, in temperatures below +3°C or above +25°C, to elevations in direct sunlight or to substrates that are hot. Coverage rates are approx. and do not take into account wastage and uneven substrates.

Breathable Primer For Improved Adhesion

ecorend S10 Bonding Primer is a silicone resin-based primer, specifically designed for use on masonry substrates. The fine particle size polymers within the product ensure deep penetration into the substrate, creating ultra-high adhesion, whilst the silicone resin ensures that the primer matches the breathability of its subsequent topcoats.

Technical Data

Pack Size	5L & 25L Jerry Can
Application Tool	Brush, Roller or Spray
Dilution Rate	Apply Neat
Coverage	Approx. 3.2 to 5m ² per litre dependent on the nature and porosity of the surface
Humidity Requirement	Less than 85%
Application Temperature	+3°C to 25°C for a minimum of 24 hours

Approved Substrates

Approved Substrates	Not Approved Substrates
New Concrete Block	Timber
Smooth Brick	Metal
Rough Brick	Glass
Hacked Off Render	Below DPC
Lightweight Block	Flat Surfaces
Render Carrier Board	Insulation

